



MORTISE LOCK WITH WHISPER COMFORT SOUND INSULATION

Manufacturer: Schulte-Schlagbaum AG

Dimensions, load and permanent functional values according to DIN 18251-1, class 4, for landing doors
For single-leaf wooden and steel doors opening outwards or inwards, prepared for profile cylinders

ADVANTAGES

- Mortise lock to DIN 18251-1, class 4
- Silent closing of the door due to whisper-comfort sound insulation
- Blocking latch against burglary with the aid of check cards or similar, even if no locking has taken place
- For use in doors with increased security requirements
- No manual locking of the door necessary
- Maintenance-free due to lifetime lubrication
- If required also for fire and smoke protection doors
- 'Made in Germany'

Specifics

Backset	55 mm / 65 mm / 80 mm	Dimensions	
Distance	72 mm	Height without forend	165 mm Tolerance: 0.5 mm
Nut width, square	8 mm / 9 mm	Height with forend	235 mm Tolerance: 0.5 mm
Forend dimensions	18 mm / 20 mm / 24 mm	Depth with forend	Backset + 32 mm Tolerance: 0.5 mm
Material	Stainless steel Latch and deadbolt made of steel, nickel-plated Lock case made of galvanized steel	Width without forend	15,5 mm Tolerance: 0.5 mm
Other specifics	Emergency opening with key	Width with forend 18	18 mm Tolerance: 0.5 mm
		Width with forend 20	20 mm Tolerance: 0.5 mm
		Width with forend 24	24 mm Tolerance: 0.5 mm

Errors and modifications reserved.